

I CLAIM

1. A device for preventing short nails of a nailing gun from being deadlocked, said device comprising a nail gun, a nail cartridge and a slot sealing member:

5        Said nailing gun having its front end formed with a gunpoint, said gunpoint having its lower side bored with a nail inlet, said gunpoint having its interior transversely formed with a nail guiding surface communicating with said nail inlet:

10        Said nail cartridge assembled under said nail inlet of said gunpoint, said nail cartridge having its topside bored with a nail outlet for a nail of a nail row to be loaded therein, said nail inlet of said gunpoint having its front part exceeding said nail outlet by a certain  
15 distance and forming a slot for receiving a long nail formed in a row therein, said long nail pushed outward from said nail outlet of said cartridge, said long nail loaded in said gunpoint through said nail inlet to be struck:

20        Said nail inlet of said gunpoint having one side transversely bored with an accommodating groove at a preset location, said accommodating groove having its topside positioned flush with said nail guiding surface of said gunpoint, said gunpoint having its lower side  
25 bored with a threaded hole at a preset location of the same side of said accommodating groove: and

      Said slot sealing member having its topside formed

with an elongate slot sealing portion, said elongate slot  
sealing portion received in said accommodating groove  
of said gunpoint, said slot sealing portion having its  
upper side formed with a sealing surface flush with said  
5 nail guiding surface of said gunpoint, said sealing  
portion of said slot sealing member having the outer side  
near its intermediate section provided with a vertical  
connect portion extending downward, said connect  
portion extending outward horizontally and forming a  
10 pivotal portion, said pivotal portion bored with a long  
sliding groove, an adjusting bolt inserted through said  
long sliding groove and screwed with said threaded hole  
of said gunpoint, said adjusting bolt adjustable in  
tightness to permit said slot sealing member to shift,  
15 said slot sealing member able to be moved transversely  
to seal up or move away from said front slot of said nail  
inlet of said gunpoint.

20

25